

SVL

Vibrofinitrice per cemento Vibrating concrete screed

Profilo a L / L profile

Dati tecnici / Technical data

Motore / Motor	Honda GX-35 - 4 tempi / 4 stroke
Potenza / Power	1 kW - 1,3 Hp a 7000 rpm
Peso / Weight	15,8 kg
Larghezza della livella / Width of profile	125 mm
Lunghezza profilo alluminio / Length of aluminium profile	1,5 - 2 - 2,5 - 3 - 4 - 5 mt
Frequenza / Frequency	9000 V.p.m.
Forza centrifuga / Centrifugal force	200 kp

**BENZINA
PETROL**



**FORNITA SENZA PROFILO
EQUIPPED WITHOUT PROFILE**

Cod: SVL



Accessori / Accessories

Per modelli SLE - SL - STL For models SLE - SL - STL

Profilo alluminio L / Aluminium L profile - L. 1,5 mt

Cod: PRO-SL 1500

Profilo alluminio L / Aluminium L profile - L. 2 mt

Cod: PRO-SL 2000

Profilo alluminio L / Aluminium L profile - L. 2,5 mt

Cod: PRO-SL 2500

Profilo alluminio L / Aluminium L profile - L. 3 mt

Cod: PRO-SL 3000

Profilo alluminio L / Aluminium L profile - L. 4 mt

Cod: PRO-SL 4000

Profilo alluminio V / Aluminium V profile - L. 5 mt

Cod: PRO-SL 5000

Per modelli SVL For models SVL

Profilo alluminio L / Aluminium L profile - L. 1,5 mt

Cod: PRO-SVL 1500

Profilo alluminio L / Aluminium L profile - L. 2 mt

Cod: PRO-SVL 2000

Profilo alluminio L / Aluminium L profile - L. 2,5 mt

Cod: PRO-SVL 2500

Profilo alluminio L / Aluminium L profile - L. 3 mt

Cod: PRO-SVL 3000

Profilo alluminio L / Aluminium L profile - L. 4 mt

Cod: PRO-SVL 4000

Profilo alluminio L / Aluminium L profile - L. 5 mt

Cod: PRO-SVL 5000